

JR972

Double Coated UPVC Tape

Description:

JR972 Is a double coated white, UPVC tape with an acrylic solvent based adhesive that offers exceptional shear strength and a high adhesion level which provides quick bonding strength.

Designed for Interior and Exterior Bonding Applications.

Product Applications:

- Banner Hems
- Mounting of Nameplates, Trophies, Labels and Signs
- Wood and Decorative Trim such as PVC Profiles for the Furniture Industry
- License Plate Frames

Features and Benefits:

- Excellent Plasticizer Migration Resistance
- Quick stick and Easy Tear or Punch
- Good Resistance to Solvents, Chemicals, UV and Heat
- Affixes Decorative Trim such as PVC Profiles

Innotec of Wisconsin, Inc.
1220 Mound Ave Suite #140
Racine, WI 53404

www.innotape.com

Technical Data Sheet

Nominal Values:

The following data are nominal values based on PSTC, ASTM and other industry standard test. The data should not be considered as exact specifications.

Carrier:	UPVC film
Adhesive:	Acrylic
Adhesion to Steel: (oz/inch of width) PSTC-1	88 oz/inch
Tensile Strength: (lbs/inch of width) PSTC-31	15.4 lbs/inch
Elongation: (at break)	150%
Thickness: (mil) PSTC-33	8.3 mil
Temperature Range: Operating - °F	-22°F~194°F
Color:	White



Phone: 1-800-776-7194
WI: 262-637-7103
Fax: 262-637-8205

sales@innotape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.