

TH400		Technical Data Sheet	
Double Coated Tissue Tape			
Description: TH400 is a double coated. General-purpose, hand-tear tape with an acrylic based adhesive. Similar to TH958, with slightly less adhesive coat weight. Ideal for many economical and temporary holding requirement applications. Designed for Interior Bonding Applications.	Nominal Values: The following data are nominal values based on PSTC, ASTM and other industry standard test. The data should not be considered as exact specifications.		
	Carrier:	Tissue	
Product Applications: <ul style="list-style-type: none">• Splicing Industrial Applications• Mounting of Nameplates, Trophies and Signage• Bonding for sporting goods: Tennis Shoes, Leather etc.	Adhesive:	Acrylic	
	Adhesion to Steel: (oz/inch of width) ASTM3121-94	44 oz/inch	
	Tensile Strength: (lbs/inch of width)	N/A	
	Elongation: (at break)	N/A	
	Total Thickness: (mil) PSTC-33	3.5 mil	
	Temperature Range: Operating - °F	32°F~158°F	
Features and Benefits: <ul style="list-style-type: none">• Moderate adhesive to most substrates• Medium tack providing quick bonding• Utility grade for Stationary Market and Bookbinding• Excellent Electrical Resistance	Color:	Transparent	
Innotec of Wisconsin, Inc. 1220 Mound Ave Suite #140 Racine, WI 53404 www.innotape.com		Phone: 1-800-776-7194 WI: 262-637-7103 Fax: 262-637-8205 sales@innotape.com	
While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.			