



Section 1. Product and Company Identification

Product Name: Craft Plastic

Trade Name: Impact Modified Acrylic

Recommended Use: Hobbies & Crafts

Restrictions on Use: None

**Distributor:** Johnson Plastics Plus

12450 Oliver Ave. South Burnsville, MN 55337 Poison Control: In Case of Emergency: Call: 800-589-3897

Medical:911

**Information:** Call: 1-800-869-7800

Email: service@jpplus.com

#### Section 2. Hazard Identification

GHS Classification: Not Classified
GHS Label Elements: Not Applicable

**GHS Rating** 

Health 5 Flammability 4 Instability 5

Hazards During Fire-fighting:

Other Hazards: Not Applicable

**NEW GHS Hazard Categories** 

Category 1 = Severe Hazard

Category 2 = Serious Hazard

Category 3 = Moderate Hazard

Category 4 = Slight Hazard
Category 5 = Minimal Hazard

| Section 3. Composition / Information on Ingredients |             |             |      |  |
|---|-------------|-------------|------|--|
| Name  | CAS#        | % by Weight | OHSA |  |
| P (EA/MMA)  | Proprietary | 50-54       | N    |  |
| Acrylic Styrene Copolymer                           | Proprietary | 35-50       | N    |  |
| Methyl methacrylate                                 | 80-62-6     | < 0.5       | Υ    |  |
| Ethyl acrylate                                      | 140-88-5    | < 0.1       | Υ    |  |

The substance(s) marked with a "Y" in the OSHA column are idenfitied as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product. The components of this product are all on the TSCA Inventory list. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

| Section 4.                   | First Aid Measu  | res   |  |  |
|------------------------------|--|---|--|--|
| Inhalation:                  | •  | Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention. |  |  |
| Eyes:                        | Dust, fines and pro<br>minutes. Get med  | ocess vapors may irritate the eyes. Immediately flush eyes with water for at least 15 ical attention.   |  |  |
| Skin:                        | Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool under ice water or a running stream. |   |  |  |
| Ingestion:                   | No adverse health effects expected from ingestion.   |   |  |  |
| Section 5.                   | Fire-Fighting M  | easures   |  |  |
| Suitable Exting              | guishing Methods:  | Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on molten burning material.   |  |  |
| Unsuitable Ext               | inguishing Methods:  | NONE known.   |  |  |
| Hazarde During Fire-fighting |  | Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation   |  |  |

products

| Protective Equip  | ment:              | Wear self-contained b                                   | reathing apparatus and protective                        | e suit.                         |  |  |
|-------------------|--------------------|---|--|---------------------------------|--|--|
| Section 6.        | Accidental Rel     | ease Measures   |  |                                 |  |  |
| Personal Precau   | ıtions:            | See Section 8 - Expos                                   | See Section 8 - Exposure Controls / Personal Protection. |                                 |  |  |
| Environmental P   | recautions:        | No Special environme                                    | ntal precautions required.                               |                                 |  |  |
| Methods and M     |                    | inment and Cleaning Up                                  |  |                                 |  |  |
| Spill / Leak:     |                    | nt of this material should n<br>container for disposal. | ot be necessary. Sweep up or ga                          | ather material and place in     |  |  |
| Section 7.        | Handling and S     | •   |  |                                 |  |  |
| Handling:         |                    | from heat, flame and stroi                              | ng oxidizing agents.                                     |                                 |  |  |
| Storage:          |                    |   | me. Store in cool place in origina                       | al container and protect form   |  |  |
| Section 8.        |                    | rol and Personal Prot                                   | ection   |                                 |  |  |
| Exposure Limit    |                    |   |  |                                 |  |  |
| •                 | cute Exposure:     |   | ay result in irritation of upper resp                    | piratory tract                  |  |  |
|                   | er Exposure Effect |   |  |                                 |  |  |
| 3) OSHA Permi     | issible Exposure l |   | US. ACGIF Threshold                                      |                                 |  |  |
|                   |                    |   | orm:   | Inhalable particles<br>10 mg/m3 |  |  |
|                   |                    | rime weig   | ghted average  | ro mg/ms                        |  |  |
|                   |                    | F   | orm:   | Respirable particles            |  |  |
|                   |                    | Time weig   | ghted average  | 3 mg/m3                         |  |  |
|                   |                    | US. OSHA T  | able Z-1 Limits for Air Contamina                        | ants (29 CFR 1910.1000)         |  |  |
|                   |                    | F   | form:  | Respirable fraction             |  |  |
|                   |                    | I   | PEL:   | 5 mg/m3                         |  |  |
|                   |                    | _   |  | Total dust                      |  |  |
|                   |                    |   | f <b>orm:</b><br>PEL:                                    | 15 mg/m3                        |  |  |
| 4) Carcinogen     | Potential:         | <u>'</u>  |  |                                 |  |  |
| Engineering Co    |                    |   |  |                                 |  |  |
| inginooning oc    |                    | d safe handling practices                               | to minimize unnecessary exposu                           | ıre                             |  |  |
|                   |                    |   | orage and ordinary handling.                             |                                 |  |  |
|                   |                    |   | tion or if dusty conditions prevail.                     |                                 |  |  |
| Personal Prote    | ctive Equipment:   | at points of famo general                               | and the ducky contained by evani-                        |                                 |  |  |
| 0.00.1.1.10.00    |                    | ses with side shields or ch                             | emical goggles to prevent eye co                         | entact                          |  |  |
|                   |                    |   | e where eye contact can occur.                           |                                 |  |  |
|                   | •                  | •   | hing to prevent skin contact.                            |                                 |  |  |
| _                 | ·                  | •   | 9  |                                 |  |  |
| Section 9.        | Physical and C     | hemical Properties                                      |  |                                 |  |  |
| Appearance:       |                    | Various Colors  | Vapor Pressure:  | Not Applicable                  |  |  |
| Odor:             |                    | Slightly acrylic  | Vapor Density:   | Not Applicable                  |  |  |
| )H:               | Section 5 1 1      | Not applicable  | Relative Density:  | 1.19 g/cm3                      |  |  |
| Melting Point / F | reezing Point:     | No data available                                       | Solubility (ies):  | Not Applicable                  |  |  |
| Boiling Point:    |                    | No data available                                       | Partition Coefficient (N-Octanol/                        |                                 |  |  |
| Flash Point:      | 0.1                | Not applicable  | Auto-Ignition Temperature:                               | 739°F (393°C)                   |  |  |
| Evaporation Rat   |                    | Not applicable  | Decomposition Temperature:                               | >572°F (> 300°C)                |  |  |
| Flammability (so  |                    | See GHS in section 2                                    | Viscosity:   | No data available               |  |  |
| Jpper Explosive   |                    | Not applicable  | Specific Gravity:  | 1.19 Water = 1 (liquid)         |  |  |
| Lower Explosive   | : LIIIIII.         | Not applicable  | Percent Volatile:  | 0%                              |  |  |
| Section 10.       | Stability Reacti   |   |  |                                 |  |  |
| Reactivity:       |                    | No data available                                       |  |                                 |  |  |
| Chemical Stabili  | •                  | Stable  |  |                                 |  |  |
| Possibility of Ha | zardous Reactions: |   |  |                                 |  |  |
| Conditions to Ass | void:              |   | arcs, potential ignition sources, c                      | • .                             |  |  |
| Conditions to Av  | oiu.               | prolonged contact with                                  | acids, alkalis and strong oxidizir                       | iy ayenis                       |  |  |

| Incompatible Materials:           | None under normal conditions of use   |  |
|-----------------------------------|---|--|
| Hazardous Decomposition Products: | Carbon oxides, Acrylates, Methacrylates, Hazardous organic compounds            |  |
| Combustion Products:              | No data available   |  |
|                                   |   |  |
| Section 11. Toxicological Inf     | formation   |  |
| Irritation Effects                |   |  |
| Eye Irritation:                   | Solid particles may cause transient irritation from mechanical abrasion.        |  |
| Skin Irritation:                  | Not expected to cause skin irritation. Molten material may cause thermal burns. |  |
| Inhalation:                       | Not a likely route of exposure. Process fumes may cause irritation.             |  |
| Ingestion:                        | May cause a choking hazard if swallowed.  |  |

## **Additional Toxicological Information**

When used and handled according to specifications, the product does not have any harmful effects according to research and information provided by suppliers.

| Section 12. Ecological Information |   |  |  |
|------------------------------------|---|--|--|
| Eco-toxicity:                      | Toxicity to fish - No relevant studies identified.  |  |  |
| Persistence and Degradability:     | This material is not expected to be readily biodegradable.  |  |  |
| Bio-accumulate Potential:          | Product is not likely to accumulate in biological organisms.  |  |  |
| Mobility in Soil:                  | This Product has not been found to migrate through soils.   |  |  |
| Other Adverse Effects:             | This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer. |  |  |

# Section 13. Disposal Considerations

## **Disposal Methods**

Product Recommendation:

- 1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
- 2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

#### Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

# Section 14. Transportation Information UN Number: Not Relevant UN Proper Shipping Name: Not Relevant Packing Group: Not Applicable Environmental Hazards: Not Relevant Transportation in Bulk (According to Annex II of MARPOL 73/78 and IBC Code): Not Relevant Special Precautions for User: No special precautions

# Section 15. Regulatory Information

(Not meant to be all-inclusive -- selected regulations represented)

Hazard categories under criteria of SARA Title III Rules (40 CFR Part 370)

| Immediate (Acute) Health   | N | Delayed (Chronic) Health | N |
|----------------------------|---|--------------------------|---|
| Sudden Release of Pressure | N | Reactive                 | N |
| Fire                       | N |                          |   |

# INGREDIENT RELATED REGULATORY INFORMATION:

| SARA REPORTABLE QUANTITIES | CERCLA RQ | SARA TPQ |
|----------------------------|-----------|----------|
| Ethyl acrylate             | 1000 LBS  | N/A      |
| Methyl methacrylate        | 1000 LBS  | N/A      |
| P (EA/MMA)                 | N/A       | N/A      |

#### **SARA TITLE III, SECTION 313**

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. See section 2.

| Chemical Name      | CAS-No.      | De minimis concentration | Reportable Threshold: |
|--------------------|--------------|--------------------------|-----------------------|
| Ethyl acrylate     | Not assigned | Not assigned             | Not assigned          |
| Methy methacrylate | Not assigned | Not assigned             | Not assigned          |

| 12-F100611016 dGlu. GUIVI GSIGI 1140-00-0 10.10 /0 | 2-Propenoic acid, ethyl ester | 140-88-5 | 0.10% | 10000 lbs (otherwise used (no manufacturing/processing)) 25000 lbs (manufacturing and processing) |
|--|-------------------------------|----------|-------|---|
|--|-------------------------------|----------|-------|---|

## **WARNING:**

This product can expose you to chemicals including styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

### Section 16. Other Information

The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: February 2022